

Heavy Duty Cleaner



Uses

Highly effective industrial / universal cleaner. Slightly foaming and light alkaline. Dissolves all fatty and oily soiling as well as wax films after a short acting time.

Cleans not only floors but all washable and alkali resistant surfaces such as walls, doors, window frames, plastic surfaces, aluminium, synthetic fabrics etc. It's a product for most applications.

Application

Proflex MK can be used with single disc machines, automatic scrubber-driers, wet mopping, or by hand application using a bucket and cleaning cloth, pad or sponge. In case of heavy soiling and for basic cleaning, leave cleaning solution to soak for approximately 10 minutes, then rinse.

Note

Not suitable for the maintenance cleaning of floor coverings treated with self-shine dispersions, as well as for wooden, asphalt, natural rubber and painted coverings. On linoleum use only up to 500ml: 10lt water.

Dilution (to 10lt water)

Surface Cleaning: 100ml

Supplies

100ml (10) – P02197

Compounds

- < 25% non-ionic surfactants
- < 5% Soap
- Water soluble solvents
- Amines

Technical Specifications



Description	Result
Colour	Colourless
pH in concentrate	11.5 ± 0.5
Specific Gravity at 20°C	1.010 g/ml

Specifications and details are subject to change without prior notice