## Performance, long life-time and ergonomics

The MH 4M series takes mid-range hot water high pressure washers to a new level, meeting the latest productivity demands in the market. The MH 4M is equipped with our industrial NA5 pump with 3 ceramic pistons and a high efficiency 4 pole motor. And the flow activated control system improves user comfort and handling as well as overall machine reliability. The MH 4M is suited for all hot water slightly heavier cleaning applications up to 4-6 hours use per day and due to the improved fuel saving EcoPower boiler system it offers very high efficiency and quick cleaning. Service and maintenance can be carried out quickly, as all vital parts are easy to inspect and reach.

Also, the diagnostics function of the 4M will give maintenance warnings to minimize any downtime. Furthermore, service and maintenance can be carried out quickly, as all vital parts are easy to inspect and reach.

The MH 4M concept ensures the most optimal transport concept across a wide variety of surface types with the 4 large wheels and great balance.

Optimal accessory storage facilities with double lance holders, turnable hook for easy removal or winding of electrical cable, innovative spray gun holder and easy storage of detergent tanks. Together with the quick service access to all vital parts, this series will provide remarkable cleaning results, saved time and reduced costs.



Picture shown may not represent model quoted

- · High efficiency 4 pole motors
- EcoPower boiler with EcoMode function
- Brass pump head
- Flow or Pressure activated unloader system
- · Innovative design with 4 big wheels
- · Easy to transport, can even be pushed/pulled across uneven surfaces
- · Diesel oil tank with level sight
- As standard delivered with 10l external detergent tank (A) and space for an extra tank (B)
- Low fuel warning system
- Onboard diagnostics function
- Standard equipment

Model	MH 4M-130/720 FA EU 230/1/50	MH 4M-200/960 FA EU
Ref. no.	107146915	107146920
PRODUCT FEATURES		
Detergent tank	•	•
Full ceramic pistons	•	•
Single-phase	•	
Three phase		•
SilentPower - 1450 rpm motor	•	•
QuickService - innovative concept	•	•
Ergo accessory system	•	•
Hose reel		
Wdk dual detergent injector	•	•
Pump oil warning system	•	•



## Performance, long life-time and ergonomics

Model	MH 4M-130/720 FA EU 230/1/50	MH 4M-200/960 FA EU
Ref. no.	107146915	107146920
PRODUCT FEATURES		
Service indicator	•	•
Parking brake	•	•
Brass cylinder head	•	•
Fuel tank	•	•
Delayed automatic start stop	•	•
2 x detergent injector	•	•
High presure detergent system	•	•
Water flow regulation	•	•
Water break tank	•	•
Flame sensor	•	•
Spray Gun Holder	•	•
Cable Hook, turnable	•	•
Motor on-off lamp	•	•
Transportable by forklift truck	•	•
Detergent tank 10 ltr.	•	•
Fuel tank 15 ltr.	•	•
Fuel sight from outside	•	•
ECO mode feature	•	•
2 lance holder	•	•
Large wheel - 4 pcs.	•	•
Anti Stone	•	•
Storage box	•	•
Water inlet filter 50µ	•	•
Technical specifications	MH 4M-130/720 FA EU 230/1/50	MH 4M-200/960 FA EU
Pump pressure (bar/MPa)	130/13	200/20
Cleaning impact (kg/force)	3	5.1
Pump (RPM)	1450	1450
Power consumption (kW)	3.6	7.2
Voltage/phase/frequency/current (V/~/Hz/A)	230/1/50/16	400/3/50/12
Water flow Qmax/Qiec (I/h)	720/660	960/890
Water temperature (water/steam) (°C)	90/150	90/150



Fuel consumption at ΔT=45°C (kg/h)

El cable (m)

5

2.9

5

3.9

## Performance, long life-time and ergonomics

Technical specifications	MH 4M-130/720 FA EU 230/1/50	MH 4M-200/960 FA EU
Fuel tank (I)	15	15
Detergent tank (I)	A: 10 + B:	A: 10 + B:
Nozzle size	.0435	.0475
Max. inlet temperature (°C)	40	40
Ceramic pistons	3	3
Length x width x height (mm)	1010x700x1016	1010x700x1016
Weight (kg)	141	142
Recommended avg. hours of use per day	5	5

 $<sup>\</sup>bullet$  Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

