

Low Foaming HD Degreaser



Uses

Highly effective alkaline industrial / universal cleaner. Low foaming. Dissolves all fatty and oily soiling as well as wax films after a short contact time. For the cleaning of all washable surfaces such as walls, doors, window frames, floors, aluminium, painted surfaces, synthetic fabrics etc.

Application

By hand, in wet mopping equipment, single-brush machines and automatic scrubber-driers, diluted with cold or warm water. In case of heavy soiling and for basic cleaning, leave cleaning solution to soak for approximately 10 minutes, then rinse.

Note

Not suitable for the maintenance cleaning of floor coverings treated with self-shine dispersions, as well as for wooden, asphalt, natural rubber and painted coverings. On linoleum use only up to 500ml: 10lt water.

Dilution (to 10lt water)

Maintenance Cleaning: 100ml

Intermediate Cleaning: 500ml

Basic Cleaning: 2000ml

Supplies

5lt container – 01642

20lt container - 01641

Compounds

- 5-15% non ionic surfactants
- < 5% anionic surfactants
- < 5% soap
- Water soluble solvents
- Amines

Technical Specifications



Description	Result
Colour	Clear
pH in concentrate	12.0 ± 0.5
Specific Gravity at 20°C	1.020 g/ml

Specifications and details are subject to change without prior notice